

Project Hardware NQ Anti-Slip

TACTILE INDICATORS & OTHER PRODUCTS

Project Hardware NQ architectural Tactile Ground Surface Indicators are available in austenitic 316 stainless steel, and UV stable polymer. All Project Hardware NQ tactile meet the required safety standards for the Building Code of Australia (BCA), Australian and New Zealand Standards (AS/NZS:1428) and The Disability Discrimination Act (DDA)




TT-DL

Individual 316 Stainless Steel tactile indicator with Drill & Lock. Top of dome 25mm. Bottom of dome 35mm. Spigot diameter 8.5mm. Length 22mm. R13 Rated.



TT-FS

Individual 316 Stainless Steel flat tactile indicator. Top of Dome 25mm. Bottom of dome 35mm. No stem. R13 Rated.



TT-SS

Individual 316 Stainless Steel tactile indicator with stem. Top of Dome 25mm. Bottom of dome 35mm. 13mm stem. R13 Rated.



TT-SH

Individual 316 Stainless Steel tactile indicator with screw & hole. Top of Dome 25mm. Bottom of dome 35mm. R13 Rated.



TT-SC

Individual 316 Stainless Steel tactile indicator with stem & carborundum inset. Top of Dome 25mm. Bottom of dome 35mm. 8mm stem. R13 Rated.



TT-DLC

Individual 316 Stainless Steel Drill & Lock tactile indicator with carborundum inset. Top of dome 25mm. Bottom of dome 35mm. Spigot diameter 8.5mm. Length 22mm. R13 Rated.



TT-DLP

Individual 316 Stainless Steel tactile indicator with Drill & Lock technology and polymer inset. Top of dome 25mm. Bottom of dome 35mm. Spigot 8.5mm. Length 22mm. R11 Rated.




TWT-PS

TacWay Tile peel & stick adhesive backing. 300mm x 300mm UV Stable Polymeric. Colours: Black, Yellow, Grey, Ivory, Terracotta. R11 Rated.



TT-SS PLATE

316 Stainless Steel tactile indicator plate. 300mm x 600mm x 2mm base plate. Includes 72 tactile indicator buttons and 6 tapered screw holes and screws. Available with Polymeric or Carborundum infill. R13 Rated.



TT-TWP

TacWay Pad 900mm x 600mm UV Stable Polymeric Tactile Pads. Colours Black, Yellow, Grey, Ivory, Terracotta. R11 Rated



TT-TS

TacStuds. Individual UV Resistant Polymer tactile indicator. Top of dome 25mm, Bottom of dome 35mm. Spigot diameter 8mm. Stem length 22mm. R11 Rated.



TT-SD

Individual 316 Stainless Steel directional tactile indicator with spigots. 35mm x 295mm x 5mm height. 3 spigots 12mm length x 6mm diameter.



CDB-1

Tactile diamond core drill bits. High quality metal drill bit for use when core drilling into tiles & all hard surfaces for tactile installation. 100mm length. Available in 6mm, 7mm & 8mm diameters.



ADHESIVES

Mapei Tac Way Pad Adhesive in 2kg and 5kg tubs. Akepox individual tactile adhesive tubes.